

# PRODUCT DATASHEET SUN@Home Planon Plus 1200x300mm

SUN@HOME PANELS | Panel luminaires with Human Centric Lighting Technology



- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



## Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

#### **Product features**

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	35.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Inrush current	3 A
Power factor $\lambda$	≥0.5
Protection class	II
Operating mode	Mains voltage

## Photometrical data

Luminous flux	2300 lm	
Total luminous flux of contained light sources	3250 lm	
Luminous efficacy	95 lm/W	
Color temperature	22005000 K	
Reference control setting of contained light source (Kelvin)	2700 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 95	
Standard deviation of color matching	< 6 sdcm	
Flickering metric (Pst LM)	≤ 1 %	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110°	

# Dimensions & Weight

Length	1200.00 mm
Width	300.00 mm
Height	56.00 mm
Product weight	3488.00 g

HCL SMART Planon Plus 120X30 TW

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Terminal	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
With light source	Yes	

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

# **Emergency lighting**

Type of emergency light operation	Non-maintained	
Type of emergency operation test	None	
Luminous flux in maintained operation mode	-	
Luminous flux in emergency operation mode	-	

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

## **EQUIPMENT / ACCESSORIES**

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

- Complete mounting and connecting accessories included

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SUNATHOME PLANON PLUS	
PDF	Legal information	SUN@HOME	
PDF	Legal information	Legal insert residential luminaires	
PDF	Declarations of conformity	SUN@HOME Planon Plus	
PDF	Declarations of conformity UKCA	SMART WIFI AND SUNATHOME	
	CAD/BIM files	Document name	
SEP .	BIM Step 3D	Sun@Home Planon Plus 120x30	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576032	Folding box 1	76 mm x 1,229 mm x 326 mm	4044.00 g	30.45 dm <sup>3</sup>
4058075576049	Shipping box 3	1,243 mm x 247 mm x 350 mm	13620.00 g	107.46 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.