

PRODUCT DATASHEET

QBM 220-240 LS-PD CM KIT

LS PD CM KIT | Mounting kits



Areas of application

- Open offices
- Individual offices
- Conference rooms
- Classrooms
- Storage and break areas
- Stairways
- Toilets
- Entrance halls
- Industry
- Production halls

Product benefits


- Enables surface and recessed ceiling mounting

Product features

- Surface mounting box
- Recessed ceiling spring clips

TECHNICAL DATA

Dimensions & Weight



Length	66.00 mm
Mounting hole spacing, length	68.00 mm
Width	66.00 mm
Height	43.50 mm
Diameter	66.00 mm
Product weight	80.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Capabilities

Dimmable	No
Type of installation	Surface mounting

Certificates & Standards

Approval marks – approval	CE / UKCA
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

– Suitable for QBM 220-240 LS/PD CI and QBM 220-240 LS/PD HB CI

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	QBM 220-240 LS/PD

Documents and certificates		Document name
	Declarations of conformity	QBM 220-240 LS/PD
	Declarations of conformity UKCA	QBM 220-240 LS/PD

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172161466	Folding box 1	110 mm x 110 mm x 100 mm	144.00 g	1.21 dm³
4062172161473	Shipping box 48	630 mm x 460 mm x 244 mm	8032.00 g	70.71 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.