

# PRODUCT DATASHEET SMART+ MATTER Classic A53 6W 824 FILAMENT GOLD DIM E27

SMART+ MATTER FILAMENT CLASSIC shapes DIMMABLE | Classic filament bulb shapes with Matter technology Dimmable



#### Areas of application

- General illumination through smart home technology
- Professional applications (hotels, bars, boutiques etc.) utilizing dynamic and robust ambient lighting effects
- When users want to mix and match smart home products from different manufacturers
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Wireless control via app or voice control
- Seamless integration with Matter-compatible systems
- Simplified set up process due to the standard user-friendly installation steps
- Enhanced security by implementing strong encryption and authentication protocols
- Lower energy consumption than incandescent or halogen lamps

#### **Product features**

- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0) or any other Matter-compatible platforms
- Light color of the Clear version: 2700 K (Warm white), light color of the Gold version: 2400 K (Extra warm white)
- Dimmable
- Network protocol: Matter over WiFi
- Lifetime up to 15,000 h





FILAMENT GOLD DIM E27

- Compatible with Alexa, Google Home, Apple Home and other Matter-compatible platforms			

#### **TECHNICAL DATA**

## Electrical data

Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	220240 V
Nominal current	34 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	0.40
Claimed equiv. conventional lamp power	53 W
Operating mode	AC Mains

## Photometrical data


Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.93
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	680 lm
Luminous flux	680 lm
Luminous efficacy	113 lm/W
Color temperature	2400 K
Color rendering index Ra	80
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

Spectral graph SMART FILAMENT DIM

# Light technical data

Beam angle	300 °
Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

## Dimensions & Weight



Product weight	36.00 g
Diameter	60.00 mm
Maximum diameter	60 mm
Length	105.00 mm
Width	60.00 mm
Height	60.00 mm
Outer bulb [PICOS]	A60

# Lifespan

Number of switching cycles	100000
Lifespan	15000 h
Lumen maintenance at end of service lifetime	0.93

## Colors & materials

Product color	Gold
Body material	Glass

# Temperatures & operating conditions

Ambient temperature range	-2040 °C

# Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Base (standard designation)	E27
Capabilities	
Dimmable	Yes 1)
Compatible smart home technology	Amazon Alexa / Google Assistant / Apple HomeKit / Philips Hue
1) Via App	
Certificates & Standards	
Energy efficiency class	E
Energy consumption	6.00 kWh/1000h
Standards	UKCA / CE
Type of protection	IP20
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Networked standby power for CLS	<0.5
Claim of equivalent power	Yes
Chromaticity coordinate x	0.494
Chromaticity coordinate y	0.424
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.5
LED light source replaces a fluorescent light source	No

2240739

AC73898,AC73898

EPREL ID

Model number

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Extended installation guide	SMTMAT 230
PDF	Declarations of conformity	MATTER LAMP
PDF	Declarations of conformity UKCA	MATTER LAMP
	Photometric and lighting design files	Document name
	Spectral power distribution	Spectral graph SMART FILAMENT DIM

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854529948	Folding box 1	61 mm x 78 mm x 114 mm	59.00 g	0.54 dm <sup>3</sup>
4099854529955	Shipping box 4	164 mm x 130 mm x 128 mm	316.00 g	2.73 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.