

PRODUCT DATASHEET SMART+ WIFI PLUG EU

SMART+ Plug | Plug with smart socket to control non-smart devices with WiFi technology, pairable with Remote Controller



Areas of application

 Wherever non-smart devices need to be integrated into compatible smart home systems

Product benefits

- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices
- Simple connection of electric devices via standard socket
- Monitors energy usage of connected devices and tracks the energy consumption

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via LEDVANCE SMART+ WiFi Remote Controller
- $-\,$ High switching power: up to 2,300 W / 10 A
- Network protocol: WiFi (2.4 GHz)
- Energy meter
- Scheduling
- Voice control works with Hey Google or Alexa



TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Mains frequency	50 Hz

Dimensions & Weight



Product weight	97.00 g
Length	80 mm
Width	59 mm
Height	49 mm

Lifespan

Number of switching cycles	100000
----------------------------	--------

Colors & materials

Product color	White
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-10+35 °C
---------------------------	-----------

Capabilities

Compatible smart home technology	Amazon Alexa / Google Assistant	

Certificates & Standards

Standards	CE
Protection class	1
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- Disconnect devices which generate heat from the mains, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (for max. 10 A)
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Extended installation guide	SMART+ WIFI INSTALLATION GUIDE
PDF	Declarations of conformity	WiFi PLUG EU

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075537248	Folding box	61 mm x 78 mm x 96 mm	142.00 g	0.46 dm ³
4058075778245	Folding box 3	104 mm x 190 mm x 86 mm	463.00 g	1.70 dm ³
4058075537255	Shipping box 4	173 mm x 108 mm x 141 mm	642.00 g	2.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.