

## PRODUCT DATASHEET

# LED Classic A 75 DIM P 10.5W 827 Frosted E27

PARATHOM® CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



### Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

### Product benefits

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

### Product features

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim))
- Long lifetime up to 25,000 h
- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity



## TECHNICAL DATA

## Electrical data

|                                        |             |
|----------------------------------------|-------------|
| Nominal wattage                        | 10.5 W      |
| Construction wattage                   | 10.50 W     |
| Nominal voltage                        | 220...240 V |
| Claimed equiv. conventional lamp power | 75 W        |
| Nominal current                        | 55 mA       |
| Type of current                        | AC          |
| Inrush current                         | 0.3 A       |
| Operating frequency                    | 50...60 Hz  |
| Mains frequency                        | 50...60 Hz  |
| Max. lamp number on MCB B10 A          | 93          |
| Max. lamp number on MCB B16 A          | 150         |
| Total harmonic distortion              | 120 %       |
| Power factor $\lambda$                 | > 0.70      |

## Photometrical data

|                                         |            |
|-----------------------------------------|------------|
| Luminous intensity                      | - cd       |
| Luminous flux                           | 1055 lm    |
| Nominal useful luminous flux 90°        | 1055 lm    |
| Luminous efficacy                       | 100 lm/W   |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Light color                             | 827        |
| Standard deviation of color matching    | ≤6 sdcn    |
| Rated LLMF at 6,000 h                   | 0.80       |
| Flickering metric (Pst LM)              | 1.0        |
| Stroboscope effect metric (SVM)         | 0.4        |



349927\_2700K\_Evl\_5630.eps

Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 220 °    |
| Warm-up time (60 %) | < 1.00 s |
| Starting time       | < 0.5 s  |

Dimensions & Weight

|                  |           |
|------------------|-----------|
| Overall length   | 105.00 mm |
| Diameter         | 60.00 mm  |
| Maximum diameter | 60 mm     |
| Product weight   | 30.00 g   |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 105 °C       |

Lifespan

|                                              |         |
|----------------------------------------------|---------|
| Lifespan L70/B50 at 25 °C                    | 25000 h |
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.70    |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90  |

Additional product data

|                             |         |
|-----------------------------|---------|
| Base (standard designation) | E27     |
| Mercury content             | 0.0 mg  |
| Mercury-free                | Yes     |
| Design / version            | Frosted |

|                |                                                                                                               |
|----------------|---------------------------------------------------------------------------------------------------------------|
| Product remark | Dimmable (with many common dimmers, see also <a href="http://www.ledvance.com/dim">www.ledvance.com/dim</a> ) |
|----------------|---------------------------------------------------------------------------------------------------------------|

### Capabilities

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

### Certificates & Standards

|                                              |                         |
|----------------------------------------------|-------------------------|
| Energy efficiency class                      | F <sup>1)</sup>         |
| Energy consumption                           | 11.00 kWh/1000h         |
| Type of protection                           | IP20                    |
| Standards                                    | CE / ROHS / REACH / ERP |
| Photobiological safety group acc. to EN62778 | RG0                     |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Country-specific categorizations

|                 |                                |
|-----------------|--------------------------------|
| ILCOS           | DRAA/F-10,5/827-220-240-E27-60 |
| Order reference | LEDPCA75D 10,5                 |

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | E27          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | 0.00 W       |
| Claim of equivalent power                           | Yes          |
| Length                                              | 105.00 mm    |
| Height                                              | 60.00 mm     |
| Width                                               | 60.00 mm     |

|                                                      |            |
|------------------------------------------------------|------------|
| Chromaticity coordinate x                            | 0.458      |
| Chromaticity coordinate y                            | 0.410      |
| R9 Colour rendering index                            | 1          |
| Beam angle correspondence                            | SPHERE_360 |
| Survival factor                                      | 0.90       |
| Displacement factor                                  | 0.70       |
| LED light source replaces a fluorescent light source | No         |
| EPREL ID                                             | 523284     |
| Model number                                         | AC31126    |

## DOWNLOAD DATA

| Documents and certificates                                                         |                             | Document name             |
|------------------------------------------------------------------------------------|-----------------------------|---------------------------|
|    | Declarations of conformity  | LED Classic A             |
| Photometric and lighting design files                                              |                             | Document name             |
|  | Spectral power distribution | 349927_2700K_Evl_5630.eps |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075594203 | Folding box<br>1             | 60 mm x 60 mm x 111 mm               | 44.00 g      | 0.40 dm <sup>3</sup> |
| 4058075594210 | Shipping box<br>10           | 325 mm x 136 mm x 126 mm             | 533.00 g     | 5.57 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For dimming conformity see [www.ledvance.com/dim](http://www.ledvance.com/dim)
- For further products and actual information concerning LED lamps see [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)
- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.