

PRODUCT DATASHEET

PL-CN111-COB- 1800-930-40D-G1

PrevaLED® COIN 111 COB G1 | LED modules with integrated optics and heat sink



TECHNICAL DATA

Electrical data

Nominal wattage	18 W
Construction wattage	18.00 W
Claimed equiv. conventional lamp power	100 W
Nominal voltage	36 V
Input voltage range	35...38 V
Type of current	DC
Nominal current	500.000 mA

Photometrical data

Total useful luminous flux [PICOS]	1800 lm
Luminous efficacy	100 lm/W
Luminous flux	1600 lm
Luminous intensity	4100 cd
Nom. useful luminous flux 120° [PICOS]	1760 lm
Color temperature	3000 K
Color rendering index Ra	90
Light color LED	White
Light color (designation)	Warm White
Standard deviation of color matching	≤3 sdc _m
Rated peak intensity	4100 cd


Light technical data

Beam angle	40 °
Rated beam angle (half peak value)	40.00 °
Starting time	0.0 s
Warm-up time (60 %)	0.00 s

LED MODULE INFORMATION

Number of LEDs per module	1
---------------------------	---

Dimensions & Weight



Length	111.0 mm
Cable length	500.000
Width	111.00 mm
Height	52.00 mm
Diameter	111,0 mm
Product weight	425.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-25...+40 °C
Maximum temperature at tc test point	80 °C
Temperature range in operation	-25...80 °C
Performance temp. acc. to IEC 62717	55 °C

Lifespan

Nominal lamp life time	50000 h
Number of switching cycles	100000

Additional product data

Product remark	Modules perfectly matched to OSRAM OPTOTRONIC® LED drivers (see relevant table) / For current photometric data and important safety, installation and application information, see www.osram.com/led-systems. / All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values / Tolerance for optical and electrical data: +/-10%
----------------	---

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Standards	Acc. to IEC 62471 / Acc. to IEC 60598-1 / Acc. to EN 60529 / Acc. to EN 62031 / Acc. to EN 55015 / Acc. to EN 61547
Type of protection	IP20
Energy consumption	19.75 kWh/1000h
Energy efficiency class	A+

LOGISTICAL DATA

Temperature range at storage	-40...80 °C
------------------------------	-------------

DOWNLOAD DATA

Documents and certificates	Document name
 Declarations of conformity	EU Declaration of Conformity of PL-CN COB G1 family
 Certificates	685711_ENEC CUBE G3
 Certificates	CQC certificate

Photometric and lighting design files	Document name
 IES file (IES)	PL-CN111-COB-1800-930-40D-G1
 LDT file (Eulumdat)	PL CN111 COB 1800 930 40D G1 LDT 300420

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899541436	Folding box 1	131 mm x 118 mm x 59 mm	463.00 g	0.91 dm ³
4052899541443	Shipping box 12	280 mm x 254 mm x 209 mm	5922.00 g	14.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.