

# PRODUCT DATASHEET

## DL SLIM DN 210 18 W 3000 K WT

DOWNLIGHT SLIM ROUND | Flat downlights with integrated driver, round shape



### Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

### Product benefits

- Very slim housing
- Low installation depth
- High luminous efficacy
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- Very homogenous light
- Functional design
- Easy installation with fast connection
- Simple installation thanks to integrated driver

### Product features

- Small visible bezel
- Connector box with push wire terminal for tool-free connection



- Light guide made of non-yellowing PMMA for long lifetime


---

**TECHNICAL DATA****Electrical data**


|                                                             |                       |
|-------------------------------------------------------------|-----------------------|
| Nominal wattage                                             | 18.00 W               |
| Nominal voltage                                             | 220...240 V           |
| Mains frequency                                             | 50...60 Hz            |
| Nominal current                                             | 108 mA                |
| Inrush current                                              | 17 A                  |
| Inrush current time $T_{h50}$                               | 56 $\mu$ s            |
| Max. number of luminaires per miniature circuit breaker B16 | 44                    |
| Max. number of luminaires per miniature circuit breaker C10 | 35                    |
| Max. number of luminaires per miniature circuit breaker C16 | 56                    |
| Power factor $\lambda$                                      | 0.50                  |
| Total harmonic distortion                                   | < 20 %                |
| Protection class                                            | II                    |
| Operating mode                                              | Integrated LED driver |

**Photometrical data**

|                                              |                      |
|----------------------------------------------|----------------------|
| Luminous flux                                | 1530 lm              |
| Luminous efficacy                            | 85 lm/W              |
| Color temperature                            | 3000 K               |
| Light color (designation)                    | Warm White           |
| Color rendering index Ra                     | > 80                 |
| Standard deviation of color matching         | < 6 sdc <sub>m</sub> |
| Luminous intensity                           | -                    |
| Flickering metric (Pst LM)                   | -                    |
| Stroboscope effect metric (SVM)              | -                    |
| Photobiological safety group acc. to EN62778 | RG0                  |
| Photobiological safety group acc. to EN62471 | RG0                  |
| Beam angle                                   | 120 °                |




4058075052345 DL SLIM DN210 18W 3000K WT IP20



4058075052345 DL SLIM DN210 18W 3000K WT IP20

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 225.00 mm |
| Height         | 30.00 mm  |
| Product weight | 435.00 g  |



Materials & Colors

|               |       |
|---------------|-------|
| Product color | White |
|---------------|-------|

|                                            |                    |
|--------------------------------------------|--------------------|
| Housing color                              | White              |
| Body material                              | Polycarbonate (PC) |
| Cover material                             | Polycarbonate (PC) |
| Light emitting surface material            | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

### Application & Mounting

|                                        |                            |
|----------------------------------------|----------------------------|
| Ambient temperature range              | -20...+50 °C               |
| Temperature range at storage           | -30...+70 °C               |
| Type of connection                     | Screwless terminal, 2-Pole |
| Type of protection                     | IP20                       |
| Protection class IK (shock resistance) | IK03                       |
| Dimmable                               | No                         |
| Mounting type                          | Recessed                   |
| Mounting location                      | Ceiling                    |
| Application environment                | Indoor                     |
| Mounting diameter                      | 210,0 mm                   |
| Mounting depth                         | 50,0 mm                    |
| With light source                      | Yes                        |
| Replaceable light source               | No                         |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 30000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 20000 h <sup>1)</sup> |
| Lifespan L80/B50 at 25 °C  | 20000 h               |
| Lifespan L90/B10 at 25 °C  | 12000 h               |
| Number of switching cycles | 50000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

|                             |         |
|-----------------------------|---------|
| Output current              | 295 mA  |
| ECG - Output ripple current | < 6.5 % |

### Certificates & Standards

|           |               |
|-----------|---------------|
| Standards | CE / CB / EAC |
|-----------|---------------|

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Luminaire with limited surface temperature, "D sign" | No              |
| Ball shot safe                                       | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

#### Additional product data

|                       |              |
|-----------------------|--------------|
| Number of illuminants | Not relevant |
|-----------------------|--------------|

#### Accessories Optional

| Product image                                                                     | Product name            | EAN           |
|-----------------------------------------------------------------------------------|-------------------------|---------------|
|  | DL SLIM FRAME DN 210 WT | 4058075079199 |

#### EQUIPMENT / ACCESSORIES

- Surface mounting frames available as accessories

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.

#### DOWNLOAD DATA

| Documents and certificates                                                         |                             | Document name                       |
|------------------------------------------------------------------------------------|-----------------------------|-------------------------------------|
|  | Extended installation guide | User Instruction Downlight LED Slim |
|  | On-Pack-Info                | Legal Insert Downlight Slim         |
|  | Legal information           | LSI DL SLIM                         |
|  | Legal information           | Informationstext 18 Abs 4 ElektroG  |
|  | Declarations of conformity  | CE Certificate downlight Slim       |




| Documents and certificates                                                          |                                     | Document name                                 |
|-------------------------------------------------------------------------------------|-------------------------------------|-----------------------------------------------|
|    | Declarations of conformity UKCA     | DL SLIM WT IP20                               |
| Photometric and lighting design files                                               |                                     | Document name                                 |
|    | IES file (IES)                      | DL SLIM DN210 18W 3000K WT IP20               |
|    | LDT file (Eulumdat)                 | DL SLIM DN210 18W 3000K WT IP20               |
|    | ULD file (DIALux)                   | DOWNLIGHTSLIMROUND21018W3000KWT               |
|    | ROLF file (RELUX)                   | DL SLIM DN210 18W-3000K                       |
|    | UGR file (UGR table)                | 4058075052345 DL SLIM DN210 18W 3000K WT IP20 |
|    | Light distribution curve type cone  | 4058075052345 DL SLIM DN210 18W 3000K WT IP20 |
|    | Light distribution curve type polar | 4058075052345 DL SLIM DN210 18W 3000K WT IP20 |
| CAD/BIM files                                                                       |                                     | Document name                                 |
|  | BIM Revit 3D                        | Downlight Slim Round                          |
|  | CAD STEP 3D                         | DL SLIM DN 210                                |
| Tender texts                                                                        |                                     | Document name                                 |
|  | Tender documents                    | DOWNLIGHT SLIM ROUND 210 18 W 3000 K WT-EN    |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075079090 | Folding box<br>1             | 45 mm x 250 mm x 230 mm              | 518.00 g     | 2.59 dm³  |
| 4058075079106 | Shipping box<br>6            | 290 mm x 260 mm x 250 mm             | 3439.00 g    | 18.85 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.